



1. OUTSTANDING FEATURES

BLOC JELT is a varnish based on a mixture of cellulosic and acrylic nitrate and in a solvent environment. It is designed to ensure the freezing and the immunity of screwed sets. It blocks all parts exposed to vibrations on all the supports and allows guarantee control on the dismantling of equipment. It can be applied to vertical surfaces. (Exists in green and red).

2. TYPICAL APPLICATIONS

BLOC JELT finds its application in the following fields:

- Data processing,
- Hi-fi, video,
- Household electrical appliance,
- Motorcar,
- Electronics, electricity,
- Any fragile sets or components...

3. DIRECTIONS FOR USE

Well shake BLOC JELT bottle before every use. Apply the varnish by means of the paintbrush to parts perfectly extra lean and dry. Let dry about 10 minutes before switching the equipment on. Well close the bottle after use.

4. PHYSICAL AND CHEMICAL PROPERTIES

Active Ingredient:

- Appearance : Thick opaque green liquid
- Volume mass @ 20°C : 0.94 g/cm³
- Viscosity @ 20°C : 800 + /-50 cP
- Temperature of use : -40°C in +135°C
- Drying time : 10 minutes
- Flexibility : Film breaking after drying
- Thinner : Acetate of ethyl or acetate of butyle
- Resistance to solvents : Good

5. USAGE INSTRUCTIONS

Read the safety data sheet. Keep closed. Avoid inhaling vapors. Use under adequate ventilation. Do not smoke. Keep out of reach children.

6. PACKAGING AND STORAGE

Bottle of 30 ml (10 bottles per box).

Keep away from any flame or source of sparks or of ignition. Do not drill or burn after usage. Store in a dry place and in a ventilated area. Store at a temperature between 5°C and 40°C.