

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Product name : 006967 - BLOCJELT ROUGE
UFI : 649M-Y0YV-200Y-R2KD
Product code : 006967

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Industrial/Professional use spec : Industrial
For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

ITW Spraytec
42, rue Gallieni
F-92600 Asnières sur Seine - France
T +33(0)1.40.80.32.32 - F +33(0)1.40.80.32.30
infofds@itwpc.com - www.jelt.fr

1.4. Emergency telephone number

Emergency number : FRANCE :+ 33 (0)1 45 42 59 59

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre, Wolfson Unit	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0344 892 0111	

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**


Flammable liquids, Category 2 H225
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: n-butyl acetate; ethyl acetate; propan-2-ol; isopropyl alcohol; isopropanol

006967 - BLOJELT ROUGE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazard statements (CLP)	: H225 - Highly flammable liquid and vapour. H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness.
Precautionary statements (CLP)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P271 - Use only outdoors or in a well-ventilated area. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention. P403+P235 - Store in a well-ventilated place. Keep cool. P501 - Dispose of contents/container to Collection point.
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
n-butyl acetate	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1 (REACH-no) 01-2119485493-29	20 – 40	Flam. Liq. 3, H226 STOT SE 3, H336
ethyl acetate	(CAS-No.) 141-78-6 (EC-No.) 205-500-4 (EC Index-No.) 607-022-00-5 (REACH-no) 01-2119475103-46	20 – 40	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Nitrocellulose	(CAS-No.) 9004-70-0 (EC-No.) 239-069-9	< 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319
propan-2-ol; isopropyl alcohol; isopropanol	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (EC Index-No.) 603-117-00-0 (REACH-no) 01-2119457558-25	< 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
2,4-dihydroxybenzophenone	(CAS-No.) 131-56-6 (EC-No.) 205-029-4	< 1	Eye Irrit. 2, H319

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a POISON CENTER/doctor/physician if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a POISON CENTER/doctor/physician if you feel unwell.

006967 - BLOJELT ROUGE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water haze. Carbon dioxide. Foam.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.
Hazardous decomposition products in case of fire : Thermal decomposition generates : fume. Carbon dioxide. Carbon monoxide.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

006967 - BLOJELT ROUGE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Incompatible materials	: Direct sunlight. Heat sources. Sources of ignition.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

n-butyl acetate (123-86-4)

France - Occupational Exposure Limits

Local name	Acétate de n-butyle
VME (mg/m ³)	710 mg/m ³
VME (ppm)	150 ppm
VLE (mg/m ³)	940 mg/m ³
VLE (ppm)	200 ppm

Germany - Occupational Exposure Limits (TRGS 900)

TRGS 900 Local name	n-Butylacetat
TRGS 900 Occupational exposure limit value (mg/m ³)	300 mg/m ³
TRGS 900 Occupational exposure limit value (ppm)	62 ppm
TRGS 900 Limitation of exposure peaks (mg/m ³)	600 mg/m ³
TRGS 900 Limitation of exposure peaks (ppm)	124 ppm

United Kingdom - Occupational Exposure Limits

Local name	Butyl acetate
WEL TWA (mg/m ³)	724 mg/m ³
WEL TWA (ppm)	150 ppm
WEL STEL (mg/m ³)	966 mg/m ³
WEL STEL (ppm)	200 ppm

ethyl acetate (141-78-6)

France - Occupational Exposure Limits

Local name	Acétate d'éthyle
VME (mg/m ³)	1400 mg/m ³
VME (ppm)	400 ppm

Germany - Occupational Exposure Limits (TRGS 900)

TRGS 900 Local name	Ethylacetat
TRGS 900 Occupational exposure limit value (mg/m ³)	1500 mg/m ³
TRGS 900 Occupational exposure limit value (ppm)	400 ppm
TRGS 900 Limitation of exposure peaks (mg/m ³)	3000 mg/m ³
TRGS 900 Limitation of exposure peaks (ppm)	800 ppm

006967 - BLOCJELT ROUGE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ethyl acetate (141-78-6)

United Kingdom - Occupational Exposure Limits

Local name	Ethyl acetate
WEL TWA (ppm)	200 ppm
WEL STEL (ppm)	400 ppm

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)

France - Occupational Exposure Limits

Local name	propane-2-ol, alcool isopropylique, isopropanol
VLE (mg/m ³)	980 mg/m ³
VLE (ppm)	400 ppm

Germany - Occupational Exposure Limits (TRGS 900)

TRGS 900 Local name	2-Propanol, Isopropylalkohol, Isopropanol
TRGS 900 Occupational exposure limit value (mg/m ³)	500 mg/m ³
TRGS 900 Occupational exposure limit value (ppm)	200 ppm
TRGS 900 Limitation of exposure peaks (mg/m ³)	1000 mg/m ³
TRGS 900 Limitation of exposure peaks (ppm)	400 ppm

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:

In case of repeated or prolonged contact wear gloves. Nitrile rubber gloves. The choice of appropriate gloves depends not only on the material, but also on other quality criteria that may vary from one manufacturer to another. As the product is a preparation made from several substances, glove material resistance may not be calculated in advance and must be tested before use. The exact penetration time of glove material is to be determined by the manufacturer of protective gloves and respected.

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: red.
Odour	: Organic solvent.
Odour threshold	: No data available

006967 - BLOCJELT ROUGE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 77 °C
Flash point	: < 21 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1 g/cm ³
Solubility	: insoluble in water. soluble in most organic solvents.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Heating may cause a fire or explosion. Stable under normal conditions.

10.3. Possibility of hazardous reactions

None under normal conditions.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Thermal decomposition generates : fume. Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

n-butyl acetate (123-86-4)

LD50 oral rat	10760 mg/kg
LD50 dermal rabbit	> 14112 mg/kg
LC50 inhalation rat (mg/l)	23,4 mg/l/4h

006967 - BLOCJELT ROUGE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ethyl acetate (141-78-6)

LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

n-butyl acetate (123-86-4)

LC50 fish 1	18 mg/l
EC50 Daphnia 1	44 mg/l
ErC50 (algae)	647,7 mg/l
NOEC chronic algae	200 mg/l

ethyl acetate (141-78-6)

LC50 fish 1	> 100 mg/l
EC50 other aquatic organisms 1	> 100 mg/l
ErC50 (algae)	> 100 mg/l

12.2. Persistence and degradability

ethyl acetate (141-78-6)

Biodegradation	> 70 % OCDE 301 D 28 days
----------------	---------------------------

12.3. Bioaccumulative potential

n-butyl acetate (123-86-4)

Partition coefficient n-octanol/water (Log Kow)	2,3
---	-----

ethyl acetate (141-78-6)

Partition coefficient n-octanol/water (Log Pow)	0,68
---	------

006967 - BLOCJELT ROUGE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with IATA / ADR / IMDG

ADR	IMDG	IATA
14.1. UN number		
UN 1263	UN 1263	UN 1263
14.2. UN proper shipping name		
PAINT	PAINT	Paint related material
Transport document description		
UN 1263 PAINT, 3, II, (D/E)	UN 1263 PAINT, 3, II	UN 1263 Paint related material, 3, II
14.3. Transport hazard class(es)		
3	3	3
		
14.4. Packing group		
II	II	II
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Special provisions (ADR) : 163, 640D, 650, 367
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E2
Packing instructions (ADR) : P001, IBC02, R001
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4

006967 - BLOJELT ROUGE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Portable tank and bulk container special provisions (ADR) : TP1, TP8, TP28

Tank code (ADR) : LGBF

Vehicle for tank carriage : FL

Transport category (ADR) : 2

Special provisions for carriage - Operation (ADR) : S2, S20

Hazard identification number (Kemler No.) : 33

Orange plates :



Tunnel restriction code (ADR) : D/E

Transport by sea

Special provisions (IMDG) : 163

Limited quantities (IMDG) : 500 ml

Excepted quantities (IMDG) : E3

Packing instructions (IMDG) : P001

Tank instructions (IMDG) : T11

Tank special provisions (IMDG) : TP1, TP8, TP27

EmS-No. (Fire) : F-E

EmS-No. (Spillage) : S-E

Stowage category (IMDG) : E

Properties and observations (IMDG) : Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA) : E2

PCA Limited quantities (IATA) : Y341

PCA limited quantity max net quantity (IATA) : 1L

PCA packing instructions (IATA) : 353

PCA max net quantity (IATA) : 5L

CAO packing instructions (IATA) : 364

CAO max net quantity (IATA) : 60L

Special provisions (IATA) : A3, A72, A192

ERG code (IATA) : 3L

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

France

Occupational diseases : RG 84 - Affections engendrées par les solvants organiques liquides à usage professionnel

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

006967 - BLOJELT ROUGE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

Class for fire hazard : Class I-1
Store unit : 1 liter
Classification remarks : F <Flam. Liq. 2>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.